




Versorgungsspannung		Messspannung		Diff.-strommess.	Funktionen				Kommunikation					Typ	Artikelnummer
100 - 275 V AC 80 - 350 V DC	20 - 50 V AC 20 - 75 V DC	8 - 660 V LL	20 - 1090 V LL	Anzahl	Digitale Ein-/Ausgänge	Speichergröße in MB	Uhr	PT 100-Eingang	RS485	Ethernet	Local Bus	Gateway Modbus-Master	USB		
•	-	•	-	2	1	512	•	-	•	•	-	•	•	UMD 98RCM*	11.29.1110
•	-	-	•	2	1	512	•	-	•	•	-	•	•	UMD 98RCM	11.29.2110
-	•	•	-	2	1	512	•	-	•	•	-	•	•	UMD 98RCM	11.29.3110
-	•	-	•	2	1	512	•	-	•	•	-	•	•	UMD 98RCM	11.29.4110
•	-	•	-	1	1	512	•	•	•	•	-	•	•	UMD 98RCM-T*	11.29.1125
•	-	-	•	1	1	512	•	•	•	•	-	•	•	UMD 98RCM-T	11.29.2125
-	•	•	-	1	1	512	•	•	•	•	-	•	•	UMD 98RCM-T	11.29.3125
-	•	-	•	1	1	512	•	•	•	•	-	•	•	UMD 98RCM-T	11.29.4125
-	•	•	-	-	1	512	•	-	-	•	•	•	•	UMD 98LB	11.61.3131
Varianten mit 333 mV-Direktanschluss															
•	-	•	-	1	1	512	•	•	•	•	-	•	•	UMD 98RCM-T FLEX	11.29.9125
-	•	•	-	-	1	512	•	-	-	•	•	•	•	UMD 98FLEX LB	11.59.9131

\* Vorzugstypen (kurze Lieferzeiten)

Zubehör	Artikelnummer
 <p>Hutschienenadapter AH9697 (Tiefe inkl. UMD: 110 mm)</p>	81.00.9697
 <p>USB 2.0 Anschlusskabel, Typ A - mini B; 3.0m</p>	18.21.2020
 <p>Schutzhaube IP65</p>	37.00.9600